

absora

DESIGNER ACOUSTIC TILES

INSTALLATION INSTRUCTIONS

Ceiling Installation

Pre Install

The site conditions at the time of installation should be clear of dust, debris and foreign particles.

Installation should only commence once the building is fully clad, water-tight, dry and all wet processes have been completed.

Install

Before installing your tiles, it is important to ensure the grid has been installed with accordance to the local Building Code, as per manufacturers' specification and is true and square.

Tiles should be left in the install area to acclimate to room temperature.

Install all fittings and fixtures including those with penetrations through ceiling tiles i.e. heat sensors, around sprinkler heads, and light fittings.

Note: Lighting and other fixtures, must be independently supported in accordance with the structural design principles

Absora Ceiling Tiles are not designed to support lighting and other fixtures. Installer shall refer to the fixture/lighting manufacturer for grid ceiling supports.

Absora Ceiling Tiles are not to be cut to fit in off-center or edge sizes. If edge pieces and smaller dimension tiles are needed, Absora flat tiles are recommended to complete the grid. Otherwise spaces should be left open for an open ceiling.

Before installing, it is recommended to layout the tiles first to understand the pattern when installing

If Absora tiles need to be cut, it is recommended to cut with a new utility knife blade.

Absora Tiles can bend but creases can remain in tiles that are folded. This will allow installation flexibility. Simply drop tiles into place of open grid.

For rooms that are air tight, it is recommended to use grid clips.